

Dispensing & Filling System - Peristaltic Pump

FU4B-1&FC32S-1



Mainly designed for automatic filling & dispensing machine.

304sst housing has good corrosion resistance.

Controller FC32S-1 and dispensing system FU4B-1 are separated, to allow flexible mounting way. Each dispensing unit has four channels.

With modular structure, one controller can control 32 channels (8 units).

Controller adopts 7 inch industrial touchscreen interface to operate easily and friendly.

Each channel has independent membrane key and LED display, which can be used to set the channel address and calibrate the dispensing volume when system is running or stop.

Dispensing volume	0.1ml-9999.99ml (resolution: 0.01ml)
Dispensing time	0.5s-6000s (resolution: 0.01s)
Interval time	0.5s-999.9s
Dispensing cycle	0-999999, "0" means unlimited cycle
Delay time before back suction	0-60.0s
Back suction angle	0-1000°
Channel quantity	4(one dispensing unit)-32(eight dispensing units)
Display	LCD
Control mode	Off-line(Controller FC32S-1 control), On-line(external signal control or communication control)
Start/stop control signal input	1 switch signal for each dispensing unit
No bottle signal input	4 switch signals corresponding to 4 channels for each dispensing unit
Communication function	RS485 communication interface, Modbus protocol, communication parameters (address, baud rate, parity, stop bit) can be set through touchscreen
Dispensing calibration	Dispensing volume of every channel can be calibrated through percentage, volume, weight or average weight method.
Channel enable	Every channel can be set as enable or disable
Fill/Backflow	All channels can be fast filling or backflowing at high speed simultaneously or separately
Channel address	Communication address of each channel can be set through independent membrane key and displayed on independent LED
Password function	Protect the system parameters and prevent misoperation through the password function
Dispensing parameter set	Dispensing parameters can be saved as a parameter set which can be invoked easily without reset it.
Dispensing unit dimension(L×W×H)	One unit (4 channels): 663mm× 218mm× 177mm
Controller dimension(L×W×H)	228mm× 60mm× 146mm
Power supply	One unit (4 channels): AC220V±20%/300W Controller: AC90-260V/10W
Operating temperature	0°C-40°C
Relative humidity	20%-80%
IP rating	IP31
Weight	One dispensing unit: 12.13kg, controller: 1.69kg



Model (Product Code)	Pump Head	Ref. Dispensing Volume(ml)	Tubing	Ref. Dispensing time(s)	Precision	Ref. Dispensing ID(mm)	Productivity (pcs/min)
Dispensing System FU4B-1 (05.11.02A) Controller FC32S-1 (05.49.27A)	YZ1515X YZ1115 FG15-13	0.3-0.5	13 [#]	1-1.2	≤2%	≤0.5	27-30
		1.0-2.3	14 [#]			≤1.0	
		2.6-5.1	19 [#]			≤1.5	
		4.6-9.1	16 [#]			≤2.0	
		10-19	25 [#]			≤3.0	
		15-30	17 [#]			≤3.0	
	YZ2515X	8.0-17	15 [#]			≤3.0	
		12-24	24 [#]			≤3.0	
		8.5-17	15 [#]			≤3.0	
	YZ1125	15-24	24 [#]			≤3.0	
		18-36	35 [#]			≤3.0	
		25-48	36 [#]			≤3.0	
	FG25-13	9-17	15 [#]			≤3.0	
		12-24	24 [#]			≤3.0	
		0.1-0.9	2×13 [#]			≤0.5	
	DMD15-13	0.2-2.3	2×14 [#]			≤1.0	
		0.5-5.9	2×19 [#]			≤2.0	
		2.0-10	2×16 [#]			≤3.0	
		5.0-25	2×25 [#]			≤3.0	

DT: 0966.115.189 / 0902.199.166 EMAIL: tinthanhphat.kinhdoanh@gmail.com

TIN THANH PHAT CO., LTD